

# CALX

PETROLEUM 

Tel: 630-677-7241



www.calxtrading.com

## FULL SYNTHETIC MOTOR OIL

**CALX Full Synthetic Motor Oil** is a premium quality multi-grade motor oil designed for maximum engine protection even under the toughest driving conditions. It outperforms conventional motor oil, reduces friction and wear at start-up and protects your engine against performance robbing sludge and varnish deposits. It is recommended for high-powered passenger cars, light trucks, sport utility vehicles and other mobile and stationary engines.

**CALX Full Synthetic Motor Oils** are fully licensed to meet or exceed car manufacturers' ILSAC GF-5 and American Petroleum Institute (API) SN service classifications and are backwards compatible with all earlier API classifications. USGLOBAL Full Synthetic Motor Oils have been field tested to be comparable to American, European and Japanese manufacturers' requirements for: ACEA A1/B1 & A5/B5, Ford WSS-M2C930A and WSS-M2C945A (5W-20), and WSS-M2C929A and WSS-M2C946A (5W-30); Chrysler MS 6395, dexos, and GM 6094M as well as many other Ford, Honda, Mazda, Mitsubishi, GM and Chrysler vehicle requirements where a premium API SN synthetic motor oil is recommended.

### Benefits and Applications

- API Service Classification SN, SM, SL, SJ
- ILSAC GF-5 Service Certification (SAE Grades 5W-20, 5W-30 and 10W-30)
- Lower pour point reduces start-up wear during cold weather
- Full synthetic oil helps to improve fuel economy
- Compatible with conventional oils
- Excellent wear, corrosion, and rust protection
- Superior resistance to sludge and varnish deposit formation
- Designed with premium base stocks for added thermal breakdown resistance



MADE IN   
THE U.S.A.

### Typical Characteristics - Full Synthetic - V140212

SAE GRADE		0W-20	0W-30	0W-40	5W-20	5W-30	5W-40	10W-30
API SERVICE		SN/GF-5	SN/GF-5	SN	SN/GF-5	SN/GF-5	SN	SN/GF-5
API Gravity	ASTM D287	35.8	35.6	35.0	35.0	34.9	35.0	33.8
Flash Point, COC °C/°F	ASTM D92	210/410	198/388	201/394	208/406	204/399	205/401	204/399
Pour Point, °C/°F	ASTM D97	-51/-59.8	-50/-58	-48/-54.4	-48/-54.4	-48/-54.4	-38/-36.4	-42/-43.6
Viscosity @ 40°C, cSt	ASTM D445	46.3	60.5	86.2	48.7	62.7	84.0	67.3
Viscosity @ 100°C, cSt	ASTM D445	8.7	10.9	15.1	8.6	10.8	15.0	10.5
Viscosity Index	ASTM D2270	169	175	185	157	164	145	144
CCS, mPa-sec, @ °C max	ASTM D5293	6200 @ -35	6200 @ -35	6200 @ -35	6200 @ -30	6200 @ -30	6200 @ -30	7000 @ -25
Phosphorus, wt% max	ASTM D4951	0.08	0.08	0.08	0.08	0.08	0.08	0.08
Total Base No. TBN	ASTM D2896	7.9	7.9	7.9	7.9	7.9	7.9	7.9

Test Method ASTM - Typical test data are average values only. Minor variations, which do not affect performance, may occur.

HANDLING AND SAFETY INFORMATION - Refer to CALX (MSDS) Material Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

1245 Amaranth Dr. Naperville, IL 60564 Cell: 630-456-6721